## CUSTOM® Vinyl PSA is recommended for use as a bonding adhesive for the below product:

# Tred-MOR® 2580 - Dubl-Stik® commercial carpet cushion https://commercial-carpetcushion.com/carpet-cushion/tredmor-2580

Tred-MOR® 2580 Dubl-Stik® carpet cushion products have been the premium choice for hospitality and commercial public areas since 1985. With a tensile strength that's perfect for heavy foot and wheeled traffic, these cushions provide the ultimate support – reducing pile-height loss and maintaining a comfortable look and feel.

Specification Sheet - <a href="https://commercial-carpetcushion.com/document/load/tred-mor-2580-specs.pdf">https://commercial-carpetcushion.com/document/load/tred-mor-2580-specs.pdf</a> Installation guide - <a href="https://commercial-carpetcushion.com/document/load/tred-mor-dublstik.pdf">https://commercial-carpetcushion.com/document/load/tred-mor-2580-specs.pdf</a>

### **Installation:**

- Use for Tred-MOR® 2580 Dubl-Stik® commercial carpet cushion installation to substrate.
- Install with wet set method only (place into wet adhesive).
- Trowel recommendations:
  - Porous Substrate 1/16" x 1/16" x1/16" square notch.
  - Non-Porous Substrate 1/16" x 1/32" x 1/32" U-notch.
- Install above product per Flooring manufacture's technical data sheet instructions.
- Install adhesive per CUSTOM® Vinyl PSA technical data sheet instructions.

#### Notes:

Conduct ASTM F3311 Mat Bond test as needed.

Reference CRI 104 Carpet Installation Standard for Commercial Carpet. 
https://carpet-rug.org/resources/installation-standards/

#### Adhesive Options:

Vinyl PSA Pressure Sensitive Adhesive (advanced pressure sensitive adhesive, solvent and glycol free, high
moisture and pH resistance). <a href="https://www.custombuildingproducts.com/TDS/TDS-361.pdf">https://www.custombuildingproducts.com/TDS/TDS-361.pdf</a>

## **Patching Compound Options:**

- Silk™ Patching & Finishing Compound (ASTM C109 / ASTM F710 compressive strength requirements). https://www.custombuildingproducts.com/TDS/TDS244.pdf
- Tech Patch-MP Multipurpose Rapid Setting Skim Coat & Floor Patch (ASTM C109 / ASTM F710 compressive strength requirements). https://www.custombuildingproducts.com/TDS/TDS326.pdf

\*Refer to Product Technical Data Sheet for complete installation instructions, requirements and product limitations.

