


FLOORING ADHESIVE SOLUTIONS

from Custom Building Products



CUSTOM®

A QUIKRETE® COMPANY



For over 50 years, Custom Building Products has been an industry leader in flooring preparation and tile and stone installation systems.

We are introducing six new products to meet today's growing demand of multiple flooring types including vinyl, wood and carpet. Each unique product is formulated to meet the most demanding installation requirements and also meets low VOC emission standards. We are known for our product excellence and build sustainability into everything we do – and these products are no exception.

CUSTOM is proud to add Adhesive flooring products to our wide range of product offerings.

#STICKwithCUSTOM

RESILIENT AND CARPET



LVP/LVT & Carpet Tile Pressure Sensitive Adhesive

RESILIENT



Vinyl Composition Tile Adhesive



4-In-1 Hybrid Polymer Wood Adhesive



Low VOC Polymer Wood Adhesive

WOOD



4-In-1 Urethane Adhesive



Professional Urethane Adhesive

VINYL PSA

VINYL PSA is an advanced pressure sensitive adhesive designed for the challenges of today's most popular resilient and soft surface flooring. Adding to its versatility, this unique formulation allows it to be used in permanent or releasable applications. VINYL PSA is solvent and glycol free, making it ideal for projects that require low VOC's. The high moisture and pH resistance make this product ideal for even the toughest applications.

- Superior moisture resistance performance [up to 95% RH per ASTM F2170]
- Releasable or permanent installations
- Easy to spread — Resists roll-up behind trowel
- Roller or trowel applied
- Low odor, great for occupied environments



FOR USE WITH:

- LVT-LVP
- Carpet Tile
- Vinyl Sheet
- Fiberglass Sheet
- VCT



RH
95%



Working Time
24 Hours



Heavy Traffic
24 Hours

Ordering Information

ITEM CODE	SIZE	PALLET QUANTITY
VPSAT4	4 gal. (15.1 L)	48



Scan to
Learn More



Vinyl Composition Tile Adhesive

VINYL VCT

VINYL VCT adhesive is engineered to minimize dry time, while maximizing adjustable grab and slip resistance. This solvent free, low odor adhesive is ideally suited for applications where VOC's are of concern. CUSTOM's thin spread adhesive dries clear, keeping layout lines visible during installation.

- Superior moisture resistance
[up to 95% RH per ASTM F2170]
- Easy to spread – Resists roll-up behind trowel
- Clear drying formula
- Low odor, great for occupied environments



FOR USE WITH:

- Vinyl Composition Tiles*
- Vinyl Quartz Tiles
- Vinyl Asphalt Tile

* Including Large Format



RH
95%



Working Time
24 Hours



Heavy Traffic
24 Hours



Scan to
Learn More

Ordering Information

ITEM CODE	SIZE	PALLET QUANTITY
VPVCTT4	4 gal. (15.1 L)	48



RESILIENT

4-In-1 Hybrid Polymer Wood Adhesive

WOOD HP4™

WOOD HP4™ is a hybrid polymer wood-plank adhesive that does the job of four products without the use of isocyanates. Perfect for critical applications, this 4-in-1 product works as an adhesive, concrete moisture barrier, sound reducer and crack suppressant all in one. Wood HP4 delivers excellent ridge retention and superior green grab, all while being easy to trowel.

- 4-in-1 technology reduces install time and eliminates need for multiple products
- No moisture testing needed
- Moisture vapor barrier
- Bridges non-structural cracks up to 1/8"
- Excellent sound reduction properties



FOR USE WITH:

- Engineered Wood Plank and Parquet
- Engineered Bamboo
- Solid Wood Plank



RH
100%



Working Time
60 Minutes



Heavy Traffic
24 Hours



Sound Reduction
Formula



Crack
Bridging



Scan to
Learn More

Ordering Information

ITEM CODE	SIZE	PALLET QUANTITY
PHAAT4	4 gal. (15.1 L)	48

WOOD



Low VOC Polymer Wood Adhesive

WOOD ENG™

WOOD ENG™ is a high bond strength, isocyanate-free adhesive specifically developed for engineered wood plank installations. Projects move quickly using this easy to trowel product with exceptional green grab. Perfect for no-hassle installations, this low VOC adhesive can be used in occupied spaces and is easy to clean with water.

- Exceptional green grab
- No memory – plank won't pull away
- Creamy, easy-to-trowel consistency
- Low odor, great for occupied environments
- Easy clean-up with soap and water, keeps projects moving



FOR USE WITH:

- Engineered Wood Plank and Parquet
- Engineered Bamboo



RH
75%



Working Time
60 Minutes



Heavy Traffic
24 Hours



Scan to
Learn More

Ordering Information

ITEM CODE	SIZE	PALLET QUANTITY
EWAT4	4 gal. (15.1 L)	48



WOOD

4-In-1 Urethane Adhesive

WOOD UR4™

WOOD UR4™ is a supreme handling urethane adhesive that does the job of four products, all in one application. Ideal for the most critical jobs, this 4-in-1 product works as an adhesive, concrete moisture control, sound reducer and crack isolation membrane. Additionally, Wood UR4 is one of the most elastic urethanes on the market, allowing for naturally occurring expansion and contraction of wood.

- 4-in-1 technology reduces install time and eliminates need for multiple products
- Single application moisture barrier and adhesive reduces material and labor costs
- Sound reduction and crack bridging capabilities for the most challenging applications
- Highly elastic formula allows for expansion and contraction without damaging adhesive



FOR USE WITH:

- Solid Wood
- Engineered Wood
- Bamboo
- Ceramic Tile
- Natural Stone Inlays
- Plywood Panels
- Underlayments



RH
90%



Working Time
60 Minutes



Heavy Traffic
24 Hours



Sound Reduction
Formula




Scan to
Learn More

Ordering Information

ITEM CODE	SIZE	PALLET QUANTITY
UAWAT5	5 gal (18.9 L)	36

WOOD



WOOD UR™

WOOD UR™ is a professional grade, water free, urethane adhesive. This classic formulation has been developed to maximize bond strength and elasticity, while minimizing effort needed to trowel. All of this results in a reliable wood adhesive suited for any variety of small or large job.

- Easy troweling results in faster installation times
- Excellent green grab for trouble-free installations
- Superior elasticity allows for natural expansion and contraction of wood
- Low odor formulation ideal for occupied environments



FOR USE WITH:

- Solid Wood
- Engineered Wood
- Bamboo
- Ceramic Tile
- Natural Stone Inlays
- Plywood Panels
- Underlayments



RH
80%



Working Time
60 Minutes



Heavy Traffic
24 Hours



Scan to
Learn More

Ordering Information



ITEM CODE	SIZE	PALLET QUANTITY
UWAT5	5 gal (18.9 L)	36



VINYL PSA

LVP/LVT & Carpet Tile Pressure Sensitive Adhesive



Coverage

Fiberglass Sheet Goods	up to 350 sq. ft./gallon	3/8" Nap Lint Free Roller
Porous Floors	170 – 180 sq. ft./gallon	 1/16" x 1/16" x 1/16" SQ
Non-Porous Floors	220 – 260 sq. ft./gallon	 1/16" x 1/32" x 1/32" U

VINYL VCT

Vinyl Composition Tile Adhesive





Coverage

Porous Floors	220 – 260 sq. ft./gallon	 1/16" x 1/32" x 1/32" U
Non-Porous Floors	300 – 350 sq. ft./gallon	 1/16" x 1/32" x 5/64" U

WOOD HP4™

4-In-1 Hybrid Polymer Wood Adhesive




Coverage

For Moisture Control, Crack Bridging and Sound Reduction	30 – 35 sq. ft./gallon	 Shark Tooth 1/4" x 3/16"
Wood Parquet	60 – 80 sq. ft./gallon	 1/8" x 1/8" x 1/8" SQ
Solid or Engineered Wood Plank (Pre-finished or Unfinished) up to 1/2" Thick	45 – 55 sq. ft./gallon	 3/16" x 5/32" V
Engineered Wood Plank 1/2" to 5/8" Thick	40 – 50 sq. ft./gallon	 1/4" x 1/8" x 1/4" SQ

WOOD ENG™

Low VOC Polymer Wood Adhesive

Coverage




Engineered Wood Plank 1/2" to 5/8" Thick	40 – 50 sq. ft./gallon	 1/4" x 1/8" x 1/4" SQ
Wood Parquet	60 – 80 sq. ft./gallon	 1/8" x 1/8" x 1/8" SQ
Engineered Wood Plank up to 1/2" Thick	45 – 55 sq. ft./gallon	 3/16" x 5/32" V

WOOD UR4™




4-In-1 Hybrid Polymer Wood Adhesive

Coverage

FOR INSTALLATIONS THAT ARE FOR ADHESIVE ONLY

Wood Flooring > 5/8" Thick	30 – 35 sq. ft./gallon	 1/4" x 1/4" x 1/4" SQ
Solid or Engineered Wood 1/2" to 5/8" Thick	40 – 50 sq. ft./gallon	 1/4" x 1/8" x 1/4" SQ
Engineered Wood up to 1/2" Thick	45 – 55 sq. ft./gallon	 3/16" x 5/32" V




FOR INSTALLATIONS THAT REQUIRE SUBFLOOR MOISTURE PROTECTION

Wood Flooring up to 3/8" Thick	30 – 40 sq. ft./gallon	 3/16" x 3/16" V
Wood Flooring > 1/2" Thick	30 – 35 sq. ft./gallon	 1/4" x 1/4" V
Use For All Installation	30 – 35 sq. ft./gallon	 Shark Tooth 1/4" x 3/16"

WOOD UR™

Professional Urethane Adhesive

Coverage

Wood Flooring > 5/8" Thick	30 – 35 sq. ft./gallon	 1/4" x 1/4" x 1/4" SQ
Solid or Engineered Wood 1/2" to 5/8" Thick	40 – 50 sq. ft./gallon	 1/4" x 1/8" x 1/4" SQ
Engineered Wood Plank up to 1/2" Thick	45 sq. ft./gallon	 3/16" x 5/32" V

Charts are for estimating purposes. Coverage may vary based on installation practices and jobsite conditions. For more sizes, use the material calculator at CustomBuildingProducts.com or contact CUSTOM Technical Services at 800-282-8786.

The CUSTOM team strives to exceed customer expectations every single day.

Our team of customer support, technical service advisors, sales force, architectural consultants and senior leadership are ready to assist from product selection through the final installation.

With the largest network of North American manufacturing and distribution sites in the industry, we offer service like no other.

Count on CUSTOM for all your flooring preparation and tile and stone installation product needs.

WARRANTY

- **2 YEARS —**

Product only, unopened and properly stored.


- **15 YEAR SYSTEM —**


CUSTOM Adhesive and CustomTECH Floor Preparation Systems.

- **FLOOR-MATCH WARRANTY —**

CUSTOM Adhesives and CustomTECH Floor Preparation Products/Systems are warranted equal to the Flooring manufacturer's warranty term up to LIFETIME.

*See CUSTOM FLOOR-MATCH Warranty, separate document.





Customer Support:
800-272-8786

Technical Support:
800-282-8786

CustomBuildingProducts.com/FlooringAdhesives



**DOWNLOAD CUSTOM'S
MOBILE APP**

©2020 Custom Building Products. All rights reserved. The CUSTOM logo, and product logos are registered trademarks of Custom Building Products. All other trademarks are the property of their respective owners. CUSTOM may make product modifications at any time without notice. Product specifications are subject to change. Visit custombuildingproducts.com for updated technical data sheets and SDS information.

Printed in the U.S.A. ADHPLB 4/22R



CUSTOM®

A QUIKRETE® COMPANY