

Easy to Roll Pressure Sensitive Adhesive

CARPET TILE PSA

NEW!



- High tack, easy to reposition
- Easy to roll formula
- 24-Hour working time
- Signature CUSTOM color dries so layout lines are visible



#STICKwithCUSTOM

FOR USE WITH:

- Vinyl Backed
- Non PVC Backed
- Polyolefin Backed
- Felt Backed
- Bituminous Backed
- Rubber underlayment



RH
99%



Working Time
24 Hours



Heavy Traffic
24 Hours



Scan this to
learn more about
Carpet Tile PSA!



CUSTOM®

A QUIKRETE® COMPANY

CARPET TILE PSA

Easy to Roll Pressure Sensitive Adhesive

CARPET TILE PSA pressure sensitive adhesive is a quick flash, high tack solution for carpet tile. This product can be troweled or rolled and can be used in permanent or releasable applications. Carpet Tile PSA is tinted in CUSTOM's signature orange color and dries so that layout lines are visible. This low odor, low VOC product is ideal for occupied environments.

Suitable as an Adhesive:

Carpet Tile, including the following:

- Vinyl Backed Carpet
- Hybrid Resilient / Modular products
- Non-PVC
- Polyolefin
- Felt Backed
- Woven Textile Backed
- Bituminous backed carpet tiles

Contact CUSTOM Technical Services before installing products with recycled backing materials.

Acceptable Substrate Conditions:

- RH – 99 % / ASTM F2170 Relative Humidity in Concrete Floor Slabs – In-situ Probes
- MVER – up to 10 / ASTM F1869 Moisture Vapor Emission Rate
- pH [Substrate] – up to 12

* Contact Technical Services for test results/readings outside above conditions.

Suitable Substrates:

- Concrete (industry approved) installed per guidelines in ASTM F710 Standard Practice for Preparing Concrete Floors to Receive Resilient Flooring, or in ACI 302.2R-06 Guide for Concrete Slabs that Receive Moisture-Sensitive Flooring Materials
- Cement terrazzo
- Plywood and other approved wood-based substrate
- Cement-based self-leveling underlayment and patching compounds
- Properly prepared primed/sealed gypsum underlayment per ASTM F2419
- Existing well bonded vinyl composition tiles
- CustomTech™ TechMVC Moisture Vapor and Alkalinity Barrier

All surfaces / substrates above require proper surface preparation.

Applicable Standards:

- ASTM F710 Standard Practice for Preparing Concrete Floors to Receive Resilient Flooring
- ACI 2R-06 Guide for Concrete Slabs that Receive Moisture-Sensitive Flooring Materials
- ASTM F2170 Standard Test Method for Determining Relative Humidity in Concrete Floor Slabs Using in situ Prob
- ASTM F1869 Standard Test Method for Measuring Moisture Vapor Emission Rate of Concrete Subfloor Using Anhydrous Calcium Chloride
- ASTM E1745 Standard Specification for Plastic Water Vapor Retarders Used in Contact with Soil or Granular Fill under Concrete Slabs
- CRI-104-Standard for Installation of Commercial Carpet
- CRI-105- Standard for Installation of Residential Carpet Resilient Floor Covering Institute (RFCI) Recommended Work
- Practices for Removal of Resilient Floor Coverings / RFCI IP#2 – Recommended Installation Practice for Vinyl Composition Tile (VCT)

Ordering Information

ITEM CODE	SIZE	PACKAGE
CTPSAT4	4 gal. (15.1 L)	Pail

Coverage



Rough-Backed Material	170-180 sq. ft./gallon	 1/16" x 1/16" x 1/16" SQ
Smooth-Backed Materials	220-260 sq. ft./gallon	 1/16" x 1/32" x 1/32" U
Smooth-Backed Materials	up to 350 sq. ft./gallon	3/8" Nap Lint Free Roller

Chart for estimating purposes. Coverage may vary based on installation practices and jobsite conditions. For more sizes, use the material calculator at CustomBuildingProducts.com or contact CUSTOM Technical Services at 800-282-8786.

Warranty:

- **2 Years** - Product only, unopened and properly stored.
- **15 Year System** – CUSTOM Adhesive and CustomTECH Floor Preparation Systems.
- **FLOOR-MATCH Warranty** – CUSTOM Adhesives and CustomTECH Floor Preparation Products/Systems are warranted equal to the Flooring manufacturer's warranty term up to LIFETIME.

*See CUSTOM FLOOR-MATCH Warranty, separate document.

©2025 Custom Building Products. All rights reserved. The CUSTOM® logo and select product logos are registered trademarks of Custom Building Products, Inc. CUSTOM may make product modifications at any time without notice. Visit custombuildingproducts.com for updated technical data sheets and SDS information.

Custom Building Products
800-272-8786
custombuildingproducts.com/flooringadhesives

SS204 12/24N



CUSTOM®

A QUIKRETE® COMPANY