

CustomTECH[®]

FLOORING PREPARATION SYSTEMS

Self-Leveling Underlayments Designed to Outperform the Competition

- Low Prep Technology — No mechanical prep required for suitable substrates
- Cures fast and develops high early-strength for quick installation
- Exceeds ASTM requirements for resilient floor covering installations



A DIVISION OF
CUSTOM[®]
A QUIKRETE[®] COMPANY



TechLevel™ 100

Calcium Aluminate Based Self-Leveling Underlayment


- Levels floors from 3/16" to 1.5" (4.8 mm to 3.8 cm) thick
- Cures fast and develops high early-strength for quick installation
- Crack resistant



TechLevel™ WSF

Fiber Reinforced Self-Leveling Underlayment for Wood Subfloors

- No lath required for plywood and OSB subfloors
- Low Prep Technology – No mechanical prep required for suitable substrates
- Compatible with most radiant heating systems
- High flow formula has excellent handling and exceptional flow retention properties
- Can be used in place of backerboard over most applications



TechLevel™ 125

Calcium Aluminate Based Deep Pour Self-Leveling Underlayment

- High strength up to 3" (7.6 cm) in one pour for thick build applications
- Low Prep Technology – No mechanical prep required for suitable substrates
- Crack resistant formula
- Ideal for inconsistent substrates



TechLevel™ XP-1

High Performance Calcium Aluminate Based Self-Leveling Underlayment

- Greater than 5,500 PSI compressive strength
- Abrasion Resistant – Holds up to traffic during construction
- High flow formula has excellent handling and exceptional flow retention properties
- Low Prep Technology – No mechanical prep required for suitable substrates



TechLevel™ 150

Premium Calcium Aluminate Based Self-Leveling Underlayment

- High flow formula has excellent handling and exceptional flow retention properties
- Low Prep Technology – No mechanical prep required for suitable substrates
- Crack resistant
- Greater than 4,300 PSI compressive strength resilient floor covering installations



TechLevel™ LITE

High Flow Lightweight Self-Leveling Underlayment

- Lightweight, sustainable formula; superior handling and weight reduction
- Apply from feather edge up to 2" (2.5 cm) in one pour
- Superior crack resistance formula reduces shrinkage and cracks
- Exceeds ASTM requirements for resilient floor covering installations
- Exceeds ANSI requirements for tile and natural stone installations

ITEM CODE	SIZE	PACKAGE
TL10050T	50 lb. (22.68 kg)	Bag
TL12550T	50 lb. (22.68 kg)	Bag
TL15050T	50 lb. (22.68 kg)	Bag
TLWSF50T	50 lb. (22.68 kg)	Bag
TLXP150T	50 lb. (22.68 kg)	Bag
TLLW30T	30 lb. (13.6 kg)	Bag

Coverage

Typical square foot coverage per 50 lb. bag (square meter per 22.68 Kg)

ITEM CODE	COVERAGE	THICKNESS
TL10050T	22.99 - 24.10 ft ² (2.14 - 2.24 m ²)	1/4" (6.4 mm)
TL12550T	21.58 - 22.74 ft ² (2.00 - 2.11 m ²)	1/4" (6.4 mm)
TL15050T	22.99 - 24.10 ft ² (2.14 - 2.24 m ²)	1/4" (6.4 mm)
TLWSF50T	22.38 - 23.57 ft ² (2.08 - 2.19 m ²)	1/4" (6.4 mm)
TLXP150T	22.75 - 23.66 ft ² (2.11 - 2.20 m ²)	1/4" (6.4 mm)
TLLW30T	22.5 ft ² per 30 lb (2 m ² per 13.6 kg)	1/4" (6.4 mm)

Chart for estimating purposes. Coverage may vary based on installation practices and jobsite conditions. For more tile and joint sizes, use the material calculator at CustomBuildingProducts.com or contact CUSTOM Technical Services at 800-282-8786.

Warranty: Flooring Installation Systems products are backed by up-to a 25-year warranty. See CustomTechFlooring.com for full warranty information including limitations and exclusions.

©2026 Custom Building Products. All rights reserved. The CUSTOM® and CustomTech® logos, and select product logos are registered trademarks of Custom Building Products, Inc. CUSTOM may make product modifications at any time without notice. Visit customtechflooring.com for updated technical data sheets and SDS information.

Uses:

Suitable as an Underlayment for:

- Carpet
- Wood, parquet
- Vinyl composition tile (VCT)
- Sheet vinyl flooring
- Laminated flooring
- Vitreous, semi-vitreous or non-vitreous tile
- Ceramic, mosaic, quarry, cement body tile
- Impervious porcelain and glass tile
- Brick and stone veneer
- Cement-based precast terrazzo
- Natural stone tile
- Stone, terrazzo



Scan this to learn more about TechLevel!

Custom Building Products
800-272-8786
CustomTechFlooring.com
SS175 2/26R



A DIVISION OF
CUSTOM[®]
A QUIKRETE[®] COMPANY