

# GROUT SOLUTIONS

prism **SCG**

prism

**CEG**<sup>TM</sup>

POLYBLEND **HP** POLYBLEND **PLUS**

Right Grout. Right Color.  
For Any Job.



**CUSTOM**<sup>®</sup>

TILE INSTALLATION SYSTEMS

Custom Building Products is North America's leader in flooring preparation and tile and stone installation systems for residential and commercial projects. When it comes to choosing a quality grout for your next project, trust the company with the right product, performance and color selection. We know grout. Count on CUSTOM.



**prism SCG**

- Unsurpassed stain resistance
- Perfect color consistency
- High performance in wet areas
- Ready-to-use single component
- Exceeds ANSI A118.19

**prism**

- Uniform consistent color
- No efflorescence
- Stain resistant — No sealer required
- Lightweight for superior handling
- Ideal for all grout joint sizes up to 1/2" (13 mm)
- Exceeds ANSI A118.7

**POLYBLEND HP**

- Advanced color consistency
- Improved resistance to efflorescence
- One grout for all joint sizes up to 3/4" (19 mm)
- Meets ANSI A118.7

**POLYBLEND PLUS**

- Brighter, more vivid finished color
- Enhanced color consistency
- Better resistance to efflorescence
- Meets ANSI A118.7\*

\*Sanded grout only.

**CEG-IG™**

- Formulated for use in harsh environments
- High chemical, stain and temperature resistance
- Water cleanable
- Contains recycled materials which may contribute to LEED® points
- Exceeds ANSI A118.3

**CEG-Lite™**

- Chemical and stain resistant
- Lightweight formula packs tightly into joints
- Easy to work with — Uniform in color
- Contains recycled LEED® contributing materials
- Exceeds ANSI A118.3

**COMMERCIAL  
100% SILICONE  
SEALANT**

- Sealant suitable for expansion joints, wet and submerged areas
- Interior/Exterior
- Use with stone and tile
- Remains permanently flexible
- ASTM C920/C794 Compliant

CUSTOM may make product modifications at any time without notice. Product specifications are subject to change. Visit [custombuildingproducts.com](http://custombuildingproducts.com) for updated technical data sheets and SDS information.

**800-272-8786** [custombuildingproducts.com](http://custombuildingproducts.com)

©2025 Custom Building Products.

CC25 6/25R



**CUSTOM®**

**TILE INSTALLATION SYSTEMS**

## CEG-IG™ Industrial Grade 100% Solids Epoxy Grout

Square Feet / m<sup>2</sup> per Unit of Grout (2 Part A + 1 Part B)

TILE SIZE	JOINT WIDTH					
	1/16" (1.6 mm)	1/8" (3.2 mm)	3/16" (4.8 mm)	1/4" (6 mm)	3/8" (9.5 mm)	1/2" (13 mm)
1" x 1" x 1/4"	103	58	43	36	29	26
2.5 x 2.5 x 0.64 cm	9.6	5.4	4.0	3.3	2.7	2.4
4-1/4" x 4-1/4" x 1/4"	400	206	141	109	77	61
10.8 x 10.8 x 0.64 cm	37.2	19.1	13.1	10.1	7.1	5.6
12" x 12" x 3/8"	739	373	251	191	130	99
30.5 x 30.5 x 1 cm	68.6	34.7	23.4	17.7	12.0	9.2
18" x 18" x 3/8"	1104	556	373	282	191	145
45.7 x 45.7 x 1 cm	102.6	51.7	34.7	26.2	17.7	13.5
6" x 24" x 3/8"	593	300	203	154	105	81
15.2 x 61 x 1 cm	55.1	27.9	18.8	14.3	9.8	7.5
12" x 24" x 3/8"	983	495	333	251	170	130
30.5 x 61 x 1 cm	91.3	46.0	30.9	23.4	15.8	12.0

## Prism® Ultimate Performance Cement Grout

Square Feet / m<sup>2</sup> per Unit of Grout (1 Package)

Used for 1/16" to 1/2" (1.6 to 13 mm) joints

## Polyblend® HP Fine Aggregate Grout

Square Feet per 25 lb. / m<sup>2</sup> per 11.34 kg

Used for 1/16" to 3/4" (1.6 to 19 mm) joints



## Polyblend® Plus Sanded Grout

Square Feet per 25 lb. / m<sup>2</sup> per 11.34 kg



TILE SIZE	JOINT WIDTH						
	1/16" <sup>**</sup> (1.6 mm)	1/8" (3.2 mm)	3/16" (4.8 mm)	1/4" (6 mm)	3/8" (9.5 mm)	1/2" (13 mm)	3/4" <sup>***</sup> (19 mm)
1" x 1" x 1/4"	96	54	40	33	27	24	13.5
2.5 x 2.5 x 0.64 cm	8.9	5.0	3.7	3.1	2.5	2.2	1.25
4-1/4" x 4-1/4" x 1/4"	372.4	192	131	101	71	56	35.5
10.8 x 10.8 x 0.64 cm	34.6	17.8	12.2	9.4	6.6	5.2	3.3
12" x 12" x 3/8"	688	348	234	177	121	92	60.5
30.5 x 30.5 x 1 cm	63.9	32.3	21.7	16.5	11.2	8.6	5.6
18" x 18" x 3/8"	1028	518	348	262	177	135	88.5
45.7 x 45.7 x 1 cm	95.5	48.1	32.3	24.4	16.5	12.5	8.25
6" x 24" x 3/8"	552	279	189	143	98	75	49
15.2 x 61 x 1 cm	51.3	25.9	17.5	13.3	9.1	7.0	4.55
12" x 24" x 3/8"	915	461	310	234	158	121	79
30.5 x 61 x 1 cm	85	42.8	28.8	21.7	14.7	11.2	7.35

\* Prism and Polyblend HP Grout Only    \*\* Polyblend HP Grout Only

## Polyblend® Plus Non-Sanded Grout

Square Feet per 10 lb. / m<sup>2</sup> per 4.5 kg



TILE SIZE	JOINT WIDTH	
	1/16" (1.6 mm)	1/8" (3.2 mm)
1" x 1" x 1/4"	40	23
2.5 x 2.5 x 0.64 cm	3.7	2.1
4-1/4" x 4-1/4" x 1/4"	156	80
10.8 x 10.8 x 0.64 cm	14.5	7.5
12" x 12" x 3/8"	289	146
30.5 x 30.5 x 1 cm	26.8	13.6
18" x 18" x 3/8"	432	217
45.7 x 45.7 x 1 cm	40.1	20.2
6" x 24" x 3/8"	232	117
15.2 x 61 x 1 cm	21.5	10.9
12" x 24" x 3/8"	384	194
30.5 x 61 x 1 cm	35.7	18.0

Charts for estimating purposes. Coverage may vary based on installation practices and jobsite conditions. For more tile and joint sizes, use the material calculator at [CustomBuildingProducts.com](http://CustomBuildingProducts.com) or contact CUSTOM Technical Services at 800-282-8786.

# EASIEST Grout to Install... PERIOD!



## Coverage

### Prism® SCG Ultimate Performance Pre-Mixed Single Component® Grout

Square Feet per 1 Gallon Unit / m<sup>2</sup> per 3.78 L



#### TILE SIZE

#### JOINT WIDTH

	1/16" (1.6 mm)	1/8" (3.2 mm)	3/16" (4.8 mm)	1/4" (6 mm)	3/8" (9.5 mm)	1/2" (13 mm)
1" x 1" x 1/4"	55	31	23	19	15	14
2.5 x 2.5 x 0.64 cm	5.1	2.9	2.1	1.8	1.4	1.3
4-1/4" x 4-1/4" x 1/4"	213	110	75	58	41	32
10.8 x 10.8 x 0.64 cm	19.8	10.2	7.0	5.4	3.8	3.0
12" x 12" x 3/8"	393	199	134	101	69	53
30.5 x 30.5 x 1 cm	36.5	18.5	12.4	9.4	6.4	4.9
18" x 18" x 3/8"	588	296	199	150	101	77
45.7 x 45.7 x 1 cm	54.6	27.5	18.5	13.9	9.4	7.2
6" x 24" x 3/8"	315	160	108	82	56	43
15.2 x 61 x 1 cm	29.3	14.8	10.0	7.6	5.2	4.0
12" x 24" x 3/8"	523	263	177	134	91	69
30.5 x 61 x 1 cm	48.6	24.5	16.4	12.4	8.4	6.4

### CEG-Lite™ Commercial 100% Solids Epoxy Grout

Square Feet / m<sup>2</sup> per Combined 1 Part A + 1 Part B (9.5 lb./4.3 kg)

Coverage for larger size CEG-Lite (19 lb./8.6 kg) is double the values below. See our website for chart and details.



#### TILE SIZE

#### JOINT WIDTH

	1/16" (1.6 mm)	1/8" (3.2 mm)	3/16" (4.8 mm)	1/4" (6 mm)	3/8" (9.5 mm)	1/2" (13 mm)
1" x 1" x 1/4"	52	29	21	18	14	13
2.5 x 2.5 x 0.64 cm	4.8	2.7	2.0	1.7	1.3	1.2
4-1/4" x 4-1/4" x 1/4"	200	103	71	54	38	30
10.8 x 10.8 x 0.64 cm	18.6	9.6	6.6	5.1	3.5	2.8
12" x 12" x 3/8"	369	187	126	95	65	50
30.5 x 30.5 x 1 cm	34.3	17.3	11.7	8.8	6.0	4.6
18" x 18" x 3/8"	552	278	187	141	95	72
45.7 x 45.7 x 1 cm	51.3	25.8	17.3	13.1	8.8	6.7
6" x 24" x 3/8"	296	150	101	77	53	40
15.2 x 61 x 1 cm	27.5	13.9	9.4	7.1	4.9	3.8
12" x 24" x 3/8"	491	248	166	126	85	65
30.5 x 61 x 1 cm	45.6	23.0	15.5	11.7	7.9	6.0

# CUSTOM's 40 color palette complements and supports today's trends in tile and design.

**#640 Arctic White**

**#381 Bright White**

**#11 Snow White**

**#641 Cool White**

**#642 Ash**

**#545 Bleached Wood**

**#333 Alabaster**

**#10 Antique White**

**#382 Bone**

**#643 Warm Gray**

**#544 Rolling Fog**

**#115 Platinum**

**#546 Cape Gray**

**#386 Oyster Gray**

**#543 Driftwood**

**#542 Graystone**

**#165 Delorean Gray**

**#335 Winter Gray**

**#09 Natural Gray**

**#19 Pewter**

**#644 Shadow**

**#370 Dove Gray**

**#645 Steel Blue**

**#122 Linen**

**#183 Chateau**

**#172 Urban Putty**

**#380 Haystack**

**#186 Khaki**

**#135 Mushroom**

**#145 Light Smoke**

**#541 Walnut**

**#185 New Taupe**

**#105 Earth**

**#59 Saddle Brown**

**#52 Tobacco Brown**

**#646 Coffee Bean**

**#95 Sable Brown**

**#647 Brown Velvet**

**#540 Truffle**

**#60 Charcoal**

**All colors available in all grout types.**

---

**Sample colors shown approximate grout color. Final installed shade may vary with the tile type, color and porosity as well as jobsite conditions and finishing techniques.**

---

## Color Selection Tips

### Complementary

Pick a grout color similar to your tile color to create a uniform look to your floor.



### Contrast

When a contrasting grout color is used, your tile grout lines stand out highlighting tile shapes and patterns creating a checkerboard effect.



Use a qualifying system of eligible surface prep and tile setting products from CUSTOM and we'll warrant the entire tile installation for life, including materials, tile and labor to repair in the event of a defect. See [CustomBuildingProducts.com](http://CustomBuildingProducts.com) for more details.