

# ONE GROUT, ANY JOINT, MAXIMUM PERFORMANCE

**For All  
Joint Sizes  
up to 3/4"**

- High performance, fine aggregate formula provides smooth, dense finish for use in narrow or large grout joints
- Improved color consistency and resistance to efflorescence
- Easy to use — Just mix with water
- Meets ANSI 118.7 high performance grout standard without additive



## STRONGER, SMOOTHER, SMARTER.



# CUSTOM®

A QUIKRETE® COMPANY

# Polyblend® HP High Performance Fine Aggregate Grout

Polyblend® HP High Performance Fine Aggregate Grout is a new high-performance cement grout that has the added benefit of fine aggregate sand that allows for use in the smallest of grout joints. Polyblend HP meets ANSI A118.7 high-performance requirements and produces hard, dense joints that resist shrinking, cracking and wear. The fine aggregate sand fits into the smallest grout joints and eliminates the need for non-sanded grout for most installations.

## Suitable Uses:

- Use to fill all joint widths up to 3/4" (19 mm)
- May be used for both floor and wall installations
- Interior and exterior applications
- Residential and commercial applications
- Countertops, tub surrounds, showers and high traffic areas
- Submerged conditions (swimming pools, spas, water features and fountains)

## Suitable Substrates:

- Vitreous, semi-vitreous or non-vitreous tile: ceramic, mosaic, quarry, cement body tiles
- Impervious porcelain and glass tile
- Brick and stone veneer
- Cement-based precast terrazzo
- Natural stone tile

## Standards

Meets ANSI A118.7 standards

## Available Sizes

- 25 lb (11.34 kg) bag
- 10 lb (4.54 kg) box

## Coverage

- Square Feet per 25 lb. / M<sup>2</sup> per 11.34 kg
- Square Feet per 10 lb. / M<sup>2</sup> per 4.54 kg

## TILE SIZE

## JOINT WIDTH

	PER 25 LB BAG						PER 10 LB BOX		
	1/16" (1.6 mm)	1/8" (3.2 mm)	3/16" (4.8 mm)	1/4" (6.4 mm)	3/8" (9.5 mm)	1/2" (12.7 mm)	3/4" (19 mm)	1/16" (1.6 mm)	1/8" (3.2 mm)
1" x 1" x 1/4" 25 x 25 x 6.4 mm	96 8.9	54 5.0	40 3.7	33 3.1	27 2.5	24 2.2	13.5 1.25	40 3.7	23 2.1
4-1/4" x 4-1/4" x 1/4" 108 x 108 x 6.4 mm	372.4 34.6	192 17.8	131 12.2	101 9.4	71 6.6	56 5.2	35.5 3.3	156 14.5	80 7.5
12" x 12" x 3/8" 305 x 305 x 9.5 mm	688 63.9	348 32.3	234 21.7	177 16.5	121 11.2	92 8.6	60.5 5.6	289 26.8	146 13.6
18" x 18" x 3/8" 457 x 457 x 9.5 mm	1028 95.5	518 48.1	348 32.3	262 24.4	177 16.5	135 12.5	88.5 8.25	432 40.1	217 20.2
6" x 24" x 3/8" 152 x 610 x 9.5 mm	552 51.3	279 26.0	189 17.5	143 13.3	98 9.1	75 7.0	49 4.55	232 15.2	117 10.9
12" x 24" x 3/8" 305 x 610 x 9.5 mm	915 85	461 42.8	310 28.8	234 21.7	158 14.7	121 11.2	79 7.35	384 35.7	194 18

Charts for estimating purposes. Coverage may vary based on installation practices and jobsite conditions. For more tile and joint sizes, use the material calculator at [CustomBuildingProducts.com](http://CustomBuildingProducts.com) or contact CUSTOM Technical Services at 800-282-8786.

	#640 Arctic White		#382 Bone		#165 Delorean Gray		#183 Chateau		#105 Earth
	#381 Bright White		#643 Warm Gray		#335 Winter Gray		#172 Urban Putty		#59 Saddle Brown
	#11 Snow White		#544 Rolling Fog		#09 Natural Gray		#380 Haystack		#52 Tobacco Brown
	#641 Cool White		#115 Platinum		#19 Pewter		#186 Khaki		#646 Coffee Bean
	#642 Ash		#546 Cape Gray		#644 Shadow		#135 Mushroom		#95 Sable Brown
	#545 Bleached Wood		#386 Oyster Gray		#370 Dove Gray		#145 Light Smoke		#647 Brown Velvet
	#333 Alabaster		#543 Driftwood		#645 Steel Blue		#541 Walnut		#540 Truffle
	#10 Antique White		#542 Graystone		#122 Linen		#185 New Taupe		#60 Charcoal

Sample colors shown generally approximate the color of the grout. Final installed color may vary. Please use our color card or grout kit for more accurate color representation.



Select a qualifying system of Prep, Set and Grout products and CUSTOM will warranty the tile installation for life, including tile, materials and labor. See website for complete details.



Scan this to learn more about Polyblend HP!

## DOWNLOAD CUSTOM'S MOBILE APP



Custom Building Products  
800-272-8786  
[custombuildingproducts.com](http://custombuildingproducts.com)

SS226 4/26R

©2026 Custom Building Products. All rights reserved. The CUSTOM® logo and select product logos are registered trademarks of Custom Building Products, Inc. CUSTOM may make product modifications at any time without notice. Visit [custombuildingproducts.com](http://custombuildingproducts.com) for updated technical data sheets and SDS information.



# CUSTOM®

A QUIKRETE® COMPANY