

Aqua Mix® Sealer's Choice® Gold PFAS-Free

1. Product Name

Aqua Mix® Sealers Choice® Gold PFAS-Free

2. Manufacturer

Custom Building Products
11450 Technology Circle
Johns Creek, GA 30097
Customer Support: 800-272-8786
Technical Services: 800-282-8786
Email: contactus@cbpmail.net custombuildingproducts.com

3. Product Description

Aqua Mix® Sealers Choice Gold PFAS-Free is a premium, no-sheen, natural look, water-based, PFAS-free, penetrating sealer formulated to provide maximum stain protection. Allows moisture vapor transmission. Sealer protects for up to 10 years under natural exposure and routine wear. May also be used as a pre-grouting sealer.

Key Features

- Free of PFAS (Per- and polyfluoroalkyl substances also known as "Forever Chemicals")
- Premium sealer for most natural stones, tiles, and porous grout.
- Maintains the natural look of most stones.
- Maximum stain resistance up to 1 hour of exposure.
- Water-based formula
- For interior and exterior use

Limitations to the Product

- Do not allow sealer to come in contact with any non-recommended surface.
- Natural stone varies greatly in composition and porosity. ALWAYS test a small and less conspicuous area before use.
- Some lighter-colored and polished stones may have visible sealer residue left on the surface after sealing if proper application procedures are not followed.
- Sealer will not prevent surface wear or etching from acids or caustic chemicals.
- If product is allowed to dry on surface, a white film may form. If this occurs, scrub with Aqua Mix NanoScrub and a white nylon pad.

4. Technical Data

Environmental Consideration

Complies with all Federal EPA and SCAQMD standards for VOC. VOC Content <105 g/L (Low Solids Coating)

5. Instructions

General Surface Prep

Surface must be dry, clean and free of waxes, sealers, or finishes. Allow adhesives and grouts in new installations to dry a minimum of 48 hours before application. Protect surrounding surfaces prior to application. Apply only when the ambient temperature is between 50 °F - 90 °F (10 °C - 32 °C). Contact Technical Services when surface temperatures are extreme.



Aqua Mix® Sealer's Choice® Gold PFAS-Free

Application of Product

WEAR IMPERVIOUS GLOVES, such as nitrile, and eye protection when handling product. Read entire label before using. Shake container well before use. ALWAYS test a small and less conspicuous area before use.

1. Apply a liberal coat using a paint pad applicator, sponge, brush, or airless sprayer. Ensure the entire surface has been treated.
 2. If applying to a dense, polished, or honed surfaces, use a white nylon scrub pad to lightly work the sealer into the surface before it is absorbed.
 3. Allow the sealer to penetrate for up to 5 minutes or until the sealer begins to dry.
 4. Wipe the surface with a clean damp microfiber towel. Then buff with a dry microfiber towel until dry.
 5. Apply the second coat, after a minimum of 30 minutes, by repeating steps 1 through 4.
- Do not allow light foot traffic until 30 minutes after the final dry buff.
 - Keep dry for 24 hours after application.
 - Sealer will achieve maximum stain protection after 24 hours.

Product Maintenance

Clean up spills as soon as possible with a damp cloth using water or a neutral pH household cleaner to retain sealing properties after cleaning. Consistent cleaning will extend the time the sealer protects the surface. Always clean using a pH neutral cleaner which is safe for all stone, grout, tile, and AquaMix Sealers. The use of high alkalinity cleaner and harsh chemicals, and steam cleaning could negatively impact the longevity and stain resistance of the sealed surfaces and is not recommended.

Cleaning of Equipment

Clean tools with soap and water immediately after use.

Health Precautions

IMPORTANT: Read carefully before using. WEAR IMPERVIOUS GLOVES, such as nitrile, and eye protection.

WARNING: EYE & SKIN IRRITANT. May be harmful if swallowed. Do not mix with other chemical products. Avoid contact with eyes and prolonged contact with skin. Do not breathe in vapors. Do not take internally. Immediately wash contaminated body and clothing thoroughly. Use in well-ventilated areas. If eye or skin contact occurs: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If inhaled: Remove person to fresh air and keep comfortable for breathing. If swallowed: Rinse mouth. Do NOT induce vomiting. Immediately seek medical advice or attention if symptoms are significant or persist. In Emergency: 1-800-535-5053. **Contains: Isopropyl alcohol, polysiloxanes, triethoxyoctylsiloxane, and alcohols, C10-C14, ethoxylated.** Before handling read Safety Data Sheet at www.custombuildingproducts.com. **KEEP OUT OF REACH OF CHILDREN.**

Technical Services Information

For technical assistance, contact Custom Technical Services at 800- 282-8786 or visit custombuildingproducts.com. For additional product information: custombuildingproducts.com/products/aqua-mix-sealers-choice-gold

Storage

Store in a dry, temperature-controlled area. Protect from freezing. If product freezes, dispose of the product according to the Safety Data Sheet.

Product Warranty

NOTICE: Obtain the applicable **LIMITED WARRANTY** at www.custombuildingproducts.com/warranties or send a written request to Custom Building Products, Inc., Five Concourse Parkway, Atlanta, GA 30328, USA. Manufactured by or under the authority of Custom Building Products, Inc. © 2026 Quikrete International, Inc.

Aqua Mix® Sealer's Choice® Gold PFAS-Free

6. Ordering: Item Code and Sizes

COUNTRY	ITEM CODE	QUANTITY	PACKAGE
USA	030881-PF	1 pt (473 ml)	Bottle
USA	030882-4-PF	1 qt (946 ml)	Bottle
USA	AMSCPF24Z-3	24 oz (710 ml)	Bottle
USA	030883-PF	1 gallon (3.8 L)	Bottle
Canada	C030881-PF	1 pt (473 ml)	Bottle
Canada	C030882-4-PF	1 qt (946 ml)	Bottle
Canada	C030883-PF	1 gallon (3.8 L)	Bottle

Coverage

Chart for estimating purposes. Coverage will vary based on installation practices, job site conditions, and surface type. Coverage is calculated based on 2 coats being used as described in the application instructions.

Package Size	Minimum Coverage	Maximum Coverage
1 pt (473 mL)	25 ft ² (2.3 m ²)	100 ft ² (9.3 m ²)
24 oz (710 ml)	35 ft ² (3.25 m ²)	150 ft ² (13.9 m ²)
1 qt (946 ml)	50 ft ² (4.6 m ²)	200 ft ² (19 m ²)
1 gallon (3.8 L)	200 ft ² (19 m ²)	800 ft ² (74 m ²)
5 gallon (19 L)	1000 ft ² (93 m ²)	4,000 ft ² (372 m ²)
55 gallon (208.2 L)	11,000 ft ² (1,022 m ²)	44,000 ft ² (4,088 m ²)