

THE GO-TO IN LARGE AND HEAVY TILE MORTAR!



VersaBond® LHT

VersaBond LHT Professional Large and Heavy Tile Mortar is now a non-sag, non-slump product that exceeds ANSI A118.4HT requirements. The non-sag enhancement comes with the same performance and handling installers have come to expect, but with the added option of installing on walls.

- General purpose, professional grade large and heavy tile mortar for horizontal and vertical applications
- Supports large and heavy tile for flat, even installations
- Can be applied up to 3/4" (19 mm)
- Non-sag performance exceeds A118.4HT and A118.11



Scan this to
learn more about
VersaBond LHT!

WE KNOW LARGE AND HEAVY TILE. COUNT ON CUSTOM.



CUSTOM®

A QUIKRETE® COMPANY

VersaBond® LHT Professional Large and Heavy Tile Mortar

- Large and heavy tile is any tile with one or more sides 15" or longer
- Most tile installed today is large format tile
- VersaBond LHT does not shrink as it cures eliminating lippage for smooth tile installations
- Great shear bond strength for a general purpose mortar, exceeds ANSI A118.4HT

Ordering Information

ITEM CODE USA	SIZE	COLOR
VBLFTMW50	50 lb. (22.68 kg) Bag	White
VBLFTMG50	50 lb. (22.68 kg) Bag	Gray

Approximate Coverage

TROWEL SIZE	MIN COVERAGE	MAX COVERAGE
Longest side of tile 8" to 15" use 1/4" x 3/8" x 1/4" (6 x 9.5 x 6 mm) Square-Notch	60 ft² (5.6 M²)	67 ft² (6.2 M²)
Longest side of tile more than 15"+ use 1/2" x 1/2" x 1/2" (13 x 13 x 13 mm) Square-Notch	42 ft² (3.9 M²)	47 ft² (4.4 M²)
Longest side of tile more than 15"+ use 3/4" x 9/16" x 3/8" (19 x 14 x 9.5 mm) U-Notch	34 ft² (3.2 M²)	38 ft² (3.5 M²)

Recommended minimum coverage (80% for dry areas and 95% for wet areas and exteriors). Back buttering may be necessary.

Note that mortar coverage does not include backbuttering tiles. When backbuttering, consider the tile underside pattern and depth to estimate thickness and usage to add to your estimate.

Chart for estimating purposes. Coverage may vary based on installation practices and jobsite conditions. For more sizes, use the material calculator at CustomBuildingProducts.com or contact CUSTOM Technical Services at 800-282-8786.



CUSTOM offers an assortment of premium performance mortars that are ideal for large and heavy tile. See our website for details about MegaLite, ProLite and Complete Contact-LFT.

©2026 Custom Building Products. All rights reserved. The CUSTOM logo, and product logos are registered trademarks of Custom Building Products. CUSTOM may make product modifications at any time without notice. Product specifications are subject to change. Visit custombuildingproducts.com for updated technical data sheets and SDS information.

Custom Building Products
800-272-8786
custombuildingproducts.com
SS134 7/26R

