



Our Newest Lightweight is Made for Heavyweights!

NEW! VersaBond® LITE

VersaBond LITE offers all the performance of VersaBond-LFT with maximized creaminess and the benefits of a true lightweight mortar. This high bond strength formula is 30% lighter than a traditional mortar, resulting in a product that is easier to trowel and move around the jobsite. Designed for a wide variety of interior and exterior floor and wall installations, VersaBond LITE is excellent for setting large and heavy tile or stone.

- Non-sag on wall installations, non-slump for floor installations
- Exceptional creaminess and easy to trowel
- Capable of LHT applications up to 3/4" (19 mm) thick on horizontal surfaces after beat-in
- Formulated with CustomLite™ technology
- Contributes to LEED® certifications
- Exceeds ANSI A118.4HET and A118.11 without additives

**WE KNOW LARGE FORMAT TILE.
COUNT ON CUSTOM.**



Scan this to
learn more about
VersaBond LITE!

VersaBond® LITE Professional Large and Heavy Tile Mortar

- High bond strength
- Non-slump — LHT thin-set for us up to 3/4" thick
- Sag and slip resistant — immediately holds wall tiles in place
- Lightweight — 35 lbs. covers the same area as 50 lbs. of traditional mortar
- Exceptional creaminess for ease of troweling

Suitable Tile Types

- Vitreous, semi-vitreous or non-vitreous tile: ceramic, quarry, cement body tile, pavers
- Impervious porcelain and glass
- Brick and stone veneer
- Cement-based precast terrazzo
- Gauged or un-gauged natural stone tile

Ordering Information

	ITEM CODE	SIZE	COLOR
USA	VBLTMG35	35 lb (15.9 kg)	Gray
USA	VBLTMW35	35 lb (15.9 kg)	White
Canada	CVBLTMG35	35 lb (15.9 kg)	Gray
Canada	CVBLTMW35	35 lb (15.9 kg)	White

Approximate Coverage

TROWEL SIZE	MIN COVERAGE	MAX COVERAGE
Longest side of tile less than 8" use 1/4" x 1/4" x 1/4" (6 x 6 x 6 mm) Square-Notch	90 sq. ft. (8.4 m ²)	100 sq. ft. (9.3 m ²)
Longest side of tile 8" to 15" use 1/4" x 3/8" x 1/4" (6 x 9.5 x 6 mm) Square-Notch	63 sq. ft. (5.9 m ²)	70 sq. ft. (6.5 m ²)
Longest side of tile more than 15"+ use 1/2" x 1/2" x 1/2" (13 x 13 x 13 mm) Square-Notch	45 sq. ft. (4.2 m ²)	50 sq. ft. (4.6 m ²)
Longest side of tile more than 15"+ use 3/4" x 9/16" x 3/8" (19 x 14 x 9.5 mm) U-Notch	36 sq. ft. (3.3 m ²)	40 sq. ft. (3.7 m ²)

Recommended minimum coverage (80% for dry areas and 95% for wet areas and exteriors). Back buttering may be necessary.

Note that mortar coverage does not include backbuttering tiles. When backbuttering, consider the tile underside pattern and depth to estimate thickness and usage to add to your estimate.

Chart for estimating purposes. Coverage may vary based on installation practices and jobsite conditions. For more sizes, use the material calculator at CustomBuildingProducts.com or contact CUSTOM Technical Services at 800-282-8786.

Suitable Substrates

- Concrete, mortar beds, masonry, Portland cement plaster
- Cement backerboards
- Liquid-applied and waterproofing membranes such as RedGuard® Waterproofing and Crack Prevention Membrane, Custom® 9240 and RedGuard® SpeedCoat
- Crack isolation sheet membranes such as Crack Buster® Pro
- Uncoupling mats such as RedGuard® Uncoupling Mat
- Substrates treated with MBP Multi-Surface Bonding Primer
- Exterior Grade Plywood (interior residential and light commercial dry areas)
- Gypsum wallboard (interior dry areas)
- Existing ceramic tile (sound stable, properly prepared/ primed with MBP or Redgard in wet areas)
- Fully-bonded sheet vinyl flooring (sound stable, properly prepared/primed with MBP in dry areas)
- Plastic laminates (sound stable, properly prepared/ primed with MBP in dry areas)
- Cutback adhesive (see preparation instructions)



DOWNLOAD CUSTOM'S MOBILE APP



©2023 Custom Building Products. All rights reserved. The CUSTOM logo, and product logos are registered trademarks of Custom Building Products. CUSTOM may make product modifications at any time without notice. Product specifications are subject to change. Visit custombuildingproducts.com for updated technical data sheets and SDS information. LEED is a Registered Trademark of U.S.G.B.C.

Custom Building Products
800-272-8786
custombuildingproducts.com
SS213 12/22R