



VERSABOND® NOW BIGGER AND BETTER!

Our VersaBond family has grown! Our family now includes every type of mortar you need to accommodate any installation.

VersaBond®

Professional Thin-Set Mortar

#1 selling brand of tile mortar. The original you know and have trusted for decades.

VersaBond®-LFT

Professional Large Format Tile Mortar

Now with a new and improved non-sag formula, this mortar also meets ANSI A118.4T and is suitable for wall installations.

VersaBond®-LFT RS

Professional Rapid Setting Large Format Tile Mortar

When turnaround time is critical to your job success, this is the go-to for LFT installations. This new rapid set formula provides exceptional working time and grouting in under two hours!

VersaBond® LITE

Professional Large and Heavy Tile Mortar

Built for heavyweight tile installations in a truly lightweight formula! This lightweight mortar meets LEED certifications and also provides an exceptional creaminess for easy troweling.



Scan this to
learn more about
VersaBond Mortars!



CUSTOM®

TILE INSTALLATION SYSTEMS

VersaBond® Professional Thin-Set Mortar



A professional formula, all-purpose mortar, polymer-modified to provide good bond strength for floor and tile projects. VersaBond cures quickly even in cold climates and adheres to most surfaces, exceeding ANSI A118.4 and A118.11 without the need for additives.

- For most standard installations
- Fast setting even in cold weather
- Good bond strength
- Approved for industry-recommended interior and exterior applications
- Exceeds ANSI A118.4 and A118.11 standards without the need for additives

VersaBond®-LFT Professional Large Format Tile Mortar



VersaBond-LFT Professional Large Format Tile Mortar is now a non-sag, non-slump product that exceeds ANSI A118.4HT requirements. The non-sag enhancement comes with the same performance and handling installers have come to expect, but with the added option of installing on walls.

- General purpose, professional grade large format tile mortar for horizontal and vertical applications
- Supports large and heavy tile for flat, even installations
- Can be applied up to 3/4" (19 mm)
- Non-sag performance exceeds A118.4HT and A118.11

VersaBond®-LFT RS Professional Rapid Setting Large Format Tile Mortar



VersaBond-LFT RS Professional Rapid Setting mortar offers the optimal combination of working and set time. Grout in just 2 hours with the assurance of excellent open time. This non-sag, non-slump polymer modified mortar is perfect for large format porcelain, ceramic and natural stone tiles. VersaBond-LFT RS can be applied 3/4" (19 mm) thick on horizontal surfaces. Suitable for floors and walls. VersaBond-LFT RS exceeds ANSI A118.4FHT and A118.11.

- For most standard floor and wall installations
- Supports large and heavy tile for flat, even installations
- For use with in-floor heating systems
- Approved for industry-recommended interior and exterior applications
- Grout and light traffic in under 2 hours and heavy traffic in 24 hours (in temperate conditions)
- Exceeds ANSI A118.4FHT and A118.11 standards without the need for additives

VersaBond® LITE Professional Large and Heavy Tile Mortar



VersaBond LITE offers all the performance of VersaBond-LFT with maximized creaminess and the benefits of a true lightweight mortar. This high bond strength formula is 30% lighter than a traditional mortar, resulting in a product that is easier to trowel and move around the jobsite. Designed for a wide variety of interior and exterior floor and wall installations, VersaBond LITE is excellent for setting large and heavy tile or stone.

- High bond strength
- Non-slump – LHT thin-set for use up to 3/4" (19 mm) thick
- Sag and slip resistant - immediately holds wall tiles in place
- Lightweight – 35 lbs. (15.9 kg) covers the same area as 50 lbs. (22.68 kg) of traditional mortar
- Exceptional creaminess for ease of troweling
- Exceeds ANSI A118.4HET, and A118.11 without the need for additives

VersaBond® Professional Thin-Set Mortar

Ordering Information

ITEM CODE USA	ITEM CODE CANADA	SIZE	COLOR
MTSG25		25 lb (11.34 kg) Bag	Gray
MTSG50	CVBG50	50 lb (22.68 kg) Bag	Gray
MTSW50	CVBW50	50 lb (22.68 kg) Bag	White

Coverage* SQUARE FOOT COVERAGE PER 50 LB BAG (SQUARE METER PER 22.68 KG)

TROWEL SIZE	MIN COVERAGE	MAX COVERAGE
Longest side of tile less than 8" use 1/4" x 1/4" x 1/4" (6 x 6 x 6 mm) Square-Notch	85 sq. ft. (8.8 M ²)	95 sq. ft. (8.8 M ²)
Longest side of tile 8" to 15" use 1/4" x 3/8" x 1/4" (6 x 9.5 x 6 mm) Square-Notch	60 sq. ft. (5.6 M ²)	67 sq. ft. (6.2 M ²)



VersaBond® LFT Professional Large Format Tile Mortar

Ordering Information

ITEM CODE USA	ITEM CODE CANADA	SIZE	COLOR
VBLFTMG50	CVBLFTMG50	50 lb (22.68 kg) Bag	Gray
VBLFTMW50	CVBLFTMW50	50 lb (22.68 kg) Bag	White

Coverage* SQUARE FOOT COVERAGE PER 50 LB BAG (SQUARE METER PER 22.68 KG)

TROWEL SIZE	MIN COVERAGE	MAX COVERAGE
Longest side of tile 8" to 15" use 1/4" x 3/8" x 1/4" (6 x 9.5 x 6 mm) Square-Notch	60 ft ² (5.6 M ²)	67 ft ² (6.2 M ²)
Longest side of tile more than 15"+ use 1/2" x 1/2" x 1/2" (13 x 13 x 13 mm) Square-Notch	42 ft ² (3.9 M ²)	47 ft ² (4.4 M ²)
Longest side of tile more than 15"+ use 3/4" x 9/16" x 3/8" (19 x 14 x 9.5 mm) U-Notch	34 ft ² (3.2 M ²)	38 ft ² (3.5 M ²)



VersaBond® LFT RS Professional Rapid Setting Large Format Tile Mortar

Ordering Information

ITEM CODE USA	ITEM CODE CANADA	SIZE	COLOR
VBLFTMRSG50	CVBLFTMRSG50	50 lb (22.68 kg) Bag	Gray
VBLFTMRSW50	CVBLFTMRSW50	50 lb (22.68 kg) Bag	White

Coverage* SQUARE FOOT COVERAGE PER 50 LB BAG (SQUARE METER PER 22.68 KG)

TROWEL SIZE	MIN COVERAGE	MAX COVERAGE
Longest side of tile 8" to 15" use 1/4" x 3/8" x 1/4" (6 x 9.5 x 6 mm) Square-Notch	60 ft ² (5.6 M ²)	67 ft ² (6.2 M ²)
Longest side of tile more than 15"+ use 1/2" x 1/2" x 1/2" (13 x 13 x 13 mm) Square-Notch	42 ft ² (3.9 M ²)	47 ft ² (4.4 M ²)
Longest side of tile more than 15"+ use 3/4" x 9/16" x 3/8" (19 x 14 x 9.5 mm) U-Notch	34 ft ² (3.2 M ²)	38 ft ² (3.5 M ²)



VersaBond® LITE Professional Large and Heavy Tile Mortar

Ordering Information

ITEM CODE USA	ITEM CODE CANADA	SIZE	COLOR
VBLTMG35	CVBLTMG35	35 lb (15.9 kg) Bag	Gray
VBLTMW35	CVBLTMW35	35 lb (15.9 kg) Bag	White

Coverage* SQUARE FOOT COVERAGE PER 35 LB BAG (SQUARE METER PER 15.9 KG)

TROWEL SIZE	MIN COVERAGE	MAX COVERAGE
Longest side of tile less than 8" use 1/4" x 1/4" x 1/4" (6 x 6 x 6 mm) Square-Notch	90 sq. ft. (8.4 M ²)	100 sq. ft. (9.3 M ²)
Longest side of tile 8" to 15" use 1/4" x 3/8" x 1/4" (6 x 9.5 x 6 mm) Square-Notch	63 sq. ft. (5.9 M ²)	70 sq. ft. (6.5 M ²)
Longest side of tile more than 15"+ use 1/2" x 1/2" x 1/2" (13 x 13 x 13 mm) Square-Notch	45 sq. ft. (4.2 M ²)	50 sq. ft. (4.6 M ²)
Longest side of tile more than 15"+ use 3/4" x 9/16" x 3/8" (19 x 14 x 9.5 mm) U-Notch	36 sq. ft. (3.3 M ²)	40 sq. ft. (3.7 M ²)




VERSABOND FAMILY COMPARISON

	VERSABOND	VERSABOND-LFT	VERSABOND-LFT RS	VERSABOND LITE
Meets or exceeds A118.4 & A118.11	✓	✓	✓	✓
Use on floors	✓	✓	✓	✓
Use on walls		✓	✓	✓
Rapid setting			✓	
High bond strength	✓	✓	✓	✓
Lightweight				✓


SuperiorBilt® Premium Notch Trowels for Large Format Tile



50% Better Coverage Than Regular Square Notch Trowels!



12" X 12" (300 x 300 mm)
Glass Tile Set Using:
Standard Square-Notch Trowel
1/4" X 3/8" X 1/4" (6 x 9.5 x 6 mm)
White lines represent
incomplete coverage



12" X 12" (300 x 300 mm)
Glass Tile Set Using:
SuperiorBilt® Medium-Notch Trowel
Equivalent To 1/4" X 3/8" X 1/4"
(6 x 9.5 x 6 mm)
Large ridges collapse onto
smaller ones for better,
more even overall coverage

ITEM CODE	TROWEL SIZE	TILE SIZE
85-P88G	Small – Equivalent to 1/4" X 1/4" X 1/4" (6 x 6 x 6 mm) Square-Notch	Up To 8" (200 mm) Tile
85-P51G	Medium – Equivalent to 1/4" X 3/8" X 1/4" (6 x 9.5 x 6 mm) Square-Notch	From 8"-16" (200 - 400 mm) Tile
85-P99G	Large – Equivalent to 1/2" X 1/2" X 1/2" (13 x 13 x 13 mm) Square-Notch	Over 16" (400 mm) Tile

DOWNLOAD CUSTOM'S MOBILE APP



*Coverage charts are for estimating purposes. Coverage may vary based on installation practices and jobsite conditions. For more sizes, use the material calculator at CustomBuildingProducts.com or contact CUSTOM Technical Services at 800-282-8786.

©2022 Custom Building Products. All rights reserved. The CUSTOM logo, and product logos are registered trademarks of Custom Building Products. CUSTOM may make product modifications at any time without notice. Product specifications are subject to change. Visit custombuildingproducts.com for updated technical data sheets and SDS information.

Custom Building Products
800-272-8786
custombuildingproducts.com

SS215 3/22R