

VERSABOND®

EVEN BIGGER AND BETTER!

Our VersaBond family has grown! Our family now includes more options for every type of mortar you need to accommodate any installation.

VersaBond® Professional Tile Mortar
#1 selling brand of tile mortar. The original you know and have trusted for decades.

VersaBond® HP
Professional Large and Heavy Tile Mortar
Along with extended open time, this smooth and creamy formula doesn't sacrifice performance for superior handling.

VersaBond® LFT
Professional Large Format Tile Mortar
Now with a new and improved non-sag formula, this mortar also meets ANSI A118.4HT and is suitable for wall installations.

VersaBond® LFT RS
Professional Rapid Setting Large Format Tile Mortar
When turnaround time is critical to your job success, this is the go-to for LHT installations. This new rapid set formula provides exceptional working time and grouting in under two hours!

VersaBond® LITE
Professional Large and Heavy Tile Mortar
Built for heavyweight tile installations in a truly lightweight formula! This lightweight mortar meets LEED certifications and also provides an exceptional creaminess for easy troweling.

Scan this to learn more about VersaBond Mortars!

CUSTOM BUILDING PRODUCTS
CUSTOM®
TILE INSTALLATION SYSTEMS



VersaBond® Professional Tile Mortar is a professional formula, all-purpose mortar, polymer-modified to provide good bond strength for floor and tile projects. VersaBond cures quickly even in cold climates and adheres to most surfaces, exceeding ANSI A118.4 and A118.11 without the need for additives.

- Can be used as thin-set or large and heavy tile mortar
- Ideal for porcelain and ceramic tile flooring
- Good bond strength
- Approved for industry-recommended interior and exterior applications
- Exceeds ANSI A118.4H and A118.11 standards without the need for additives



VersaBond® HP High Performance Large and Heavy Tile Mortar is a high bond strength, non-sag, non-slump large and heavy tile mortar designed for applications up to 3/4" (19 mm) thick. Along with extended open time, this smooth and creamy formula doesn't sacrifice performance for superior handling. Suitable for interior and exterior floors and walls, VersaBond HP is a true universal mortar.

- Designed for a superior bond for large and heavy tiles
- Non-sag on walls, non-slump on floors
- Meets ANSI 118.15HET and ISO 13007 C2TES1P1 rated
- Superior workability — Smooth and creamy formula provides easy handling

ELIGIBLE FOR LIFETIME WARRANTY GARANTIA™



VersaBond® LFT Professional Large Format Tile Mortar is now a non-sag, non-slump product that exceeds ANSI A118.4HT requirements. The non-sag enhancement comes with the same performance and handling installers have come to expect, but with the added option of installing on walls.

- General purpose, professional grade large format tile mortar for horizontal and vertical applications
- Supports large and heavy tile for flat, even installations
- Can be applied up to 3/4" (19 mm)
- Non-sag performance exceeds A118.4HT and A118.11H



VersaBond® LFT RS Professional Rapid Setting Large Format Tile Mortar offers the optimal combination of working and set time. Grout in just 2 hours with the assurance of excellent open time. This non-sag, non-slump polymer modified mortar is perfect for large format porcelain, ceramic and natural stone tiles. VersaBond LFT RS can be applied 3/4" (19 mm) thick on horizontal surfaces. Suitable for floors and walls. VersaBond LFT RS exceeds ANSI A118.4FHT and A118.11.

- For most standard floor and wall installations
- Supports large and heavy tile for flat, even installations
- For use with in-floor heating systems
- Approved for industry-recommended interior and exterior applications
- Grout and light traffic in under 2 hours and heavy traffic in 24 hours (in temperate conditions)
- Exceeds ANSI A118.4FHT and A118.11H standards without the need for additives



VersaBond® LITE Professional Large and Heavy Tile Mortar offers all the performance of VersaBond-LFT with maximized creaminess and the benefits of a true lightweight mortar. This high bond strength formula is 30% lighter than a traditional mortar, resulting in a product that is easier to trowel and move around the jobsite. Designed for a wide variety of interior and exterior floor and wall installations, VersaBond LITE is excellent for setting large and heavy tile or stone.

- High bond strength
- Non-slump — LHT thin-set for use up to 3/4" (19 mm) thick
- Sag and slip resistant — immediately holds wall tiles in place
- Lightweight — 35 lbs. (15.9 kg) covers the same area as 50 lbs. (22.68 kg) of traditional mortar
- Exceptional creaminess for ease of troweling
- Exceeds ANSI A118.4HET, and A118.11 without the need for additives

VersaBond® Professional Thin-Set Mortar

ITEM CODE USA	ITEM CODE CANADA	SIZE	COLOR
MTSG25		25 lb (11.34 kg) Bag	Gray
MTSG50	CVBG50	50 lb (22.68 kg) Bag	Gray
MTSW50	CVBW50	50 lb (22.68 kg) Bag	White

Coverage* SQUARE FOOT COVERAGE PER 50 LB BAG (SQUARE METER PER 22.68 KG)

TROWEL SIZE	MIN COVERAGE	MAX COVERAGE
1/4" x 1/4" x 1/4" (6 x 6 x 6 mm) Square-Notch	85 sq. ft. (7.9 M²)	95 sq. ft. (8.8 M²)
1/4" x 3/8" x 1/4" (6 x 9.5 x 6 mm) Square-Notch	60 sq. ft. (5.6 M²)	67 sq. ft. (6.2 M²)



VersaBond® Professional Thin-Set Mortar

ITEM CODE USA	ITEM CODE CANADA	SIZE	COLOR
VBHPG50	CVBHPG50	50 lb (22.68 kg) Bag	Gray
VBHPW50	CVBHPW50	50 lb (22.68 kg) Bag	White

Coverage* SQUARE FOOT COVERAGE PER 50 LB BAG (SQUARE METER PER 22.68 KG)

TROWEL SIZE	MIN COVERAGE	MAX COVERAGE
1/4" x 1/4" x 1/4" (6 x 6 x 6 mm) Square-Notch	90 sq. ft. (8.4 M²)	100 sq. ft. (9.3 M²)
1/4" x 3/8" x 1/4" (6 x 9.5 x 6 mm) Square-Notch	60 sq. ft. (5.6 M²)	67 sq. ft. (6.2 M²)
3/4" x 9/16" x 3/8" (19 x 14 x 9.5 mm) U-Notch	34 sq. ft. (3.2 M²)	38 sq. ft. (3.5 M²)



VersaBond® LFT Professional Large Format Tile Mortar

ITEM CODE USA	ITEM CODE CANADA	SIZE	COLOR
VBLFTMG50	CVBLFTMG50	50 lb (22.68 kg) Bag	Gray
VBLFTMW50	CVBLFTMW50	50 lb (22.68 kg) Bag	White

Coverage* SQUARE FOOT COVERAGE PER 50 LB BAG (SQUARE METER PER 22.68 KG)

TROWEL SIZE	MIN COVERAGE	MAX COVERAGE
1/4" x 1/4" x 1/4" (6 x 6 x 6 mm) Square-Notch	90 sq. ft. (8.4 M²)	100 sq. ft. (9.3 M²)
1/4" x 3/8" x 1/4" (6 x 9.5 x 6 mm) Square-Notch	60 sq. ft. (5.6 M²)	67 sq. ft. (6.2 M²)
3/4" x 9/16" x 3/8" (19 x 14 x 9.5 mm) U-Notch	34 sq. ft. (3.2 M²)	38 sq. ft. (3.5 M²)



VersaBond® LFT RS Professional Rapid Setting Large Format Tile Mortar

ITEM CODE USA	ITEM CODE CANADA	SIZE	COLOR
VBLFTMRSG50	CVBLFTMRSG50	50 lb (22.68 kg) Bag	Gray

Coverage* SQUARE FOOT COVERAGE PER 50 LB BAG (SQUARE METER PER 22.68 KG)

TROWEL SIZE	MIN COVERAGE	MAX COVERAGE
1/4" x 3/8" x 1/4" (6 x 9.5 x 6 mm) Square-Notch	60 ft² (5.6 M²)	67 ft² (6.2 M²)
3/4" x 9/16" x 3/8" (19 x 14 x 9.5 mm) U-Notch	34 ft² (3.2 M²)	38 ft² (3.5 M²)



VersaBond® LITE Professional Large and Heavy Tile Mortar

ITEM CODE USA	ITEM CODE CANADA	SIZE	COLOR
VBLTMG35	CVBLTMG35	35 lb (15.9 kg) Bag	Gray
VBLTMW35	CVBLTMW35	35 lb (15.9 kg) Bag	White

Coverage* SQUARE FOOT COVERAGE PER 35 LB BAG (SQUARE METER PER 15.9 KG)

TROWEL SIZE	MIN COVERAGE	MAX COVERAGE
1/4" x 1/4" x 1/4" (6 x 6 x 6 mm) Square-Notch	90 sq. ft. (8.4 M²)	100 sq. ft. (9.3 M²)
1/4" x 3/8" x 1/4" (6 x 9.5 x 6 mm) Square-Notch	63 sq. ft. (5.9 M²)	70 sq. ft. (6.5 M²)
3/4" x 9/16" x 3/8" (19 x 14 x 9.5 mm) U-Notch	36 sq. ft. (3.3 M²)	40 sq. ft. (3.7 M²)



VERSABOND® FAMILY COMPARISON

	VersaBond	VersaBond HP	VersaBond-LFT	VersaBond-LFT RS	VersaBond LITE
Meets or exceeds A118.4 & A118.11	✓	✓	✓	✓	✓
Use on floors	✓	✓	✓	✓	✓
Use on walls		✓	✓	✓	✓
Rapid setting				✓	
High bond strength	✓	✓	✓	✓	✓
Lightweight					✓



ELIGIBLE FOR LIFETIME WARRANTY GARANTIA™

Select a qualifying system of Prep, Set and Grout products and CUSTOM will warranty the tile installation for life, including tile, materials and labor. See website for complete details.

GREENGUARD GOLD

DOWNLOAD CUSTOM'S MOBILE APP

Available on the App Store | ANDROID APP ON Google play

*Coverage charts are for estimating purposes. Coverage may vary based on installation practices and jobsite conditions. For more sizes, use the material calculator at CustomBuildingProducts.com or contact CUSTOM Technical Services at 800-282-8786.

©2025 Custom Building Products. All rights reserved. The CUSTOM logo, and product logos are registered trademarks of Custom Building Products. CUSTOM may make product modifications at any time without notice. Product specifications are subject to change. Visit custombuildingproducts.com for updated technical data sheets and SDS information.

Custom Building Products
800-272-8786
custombuildingproducts.com

SS215 4/25R

CUSTOM® TILE INSTALLATION SYSTEMS