

CUSTOM's Most Versatile Mortar Yet!



NEW!

VERSABOND® HP

HIGH PERFORMANCE LARGE AND HEAVY TILE MORTAR

- Designed for a superior bond for large and heavy tiles
- Non-sag on walls, non-slump on floors
- Exceeds ANSI 118.15HET and ISO 13007 C2TES1P1 rated
- Superior workability — Smooth and creamy formula provides easy handling



**WE KNOW TILE INSTALLATION.
COUNT ON CUSTOM.**



Scan this to
learn more about
VersaBond HP!



CUSTOM®
TILE INSTALLATION SYSTEMS

VersaBond® HP High Performance Large and Heavy Tile Mortar

VersaBond HP is a high bond strength, non-sag, non-slump large and heavy tile mortar designed for applications up to 3/4" (19 mm) thick. Along with extended open time, this smooth and creamy formula doesn't sacrifice performance for superior handling. Suitable for interior and exterior floors and walls, VersaBond HP is a true universal mortar.

- Non-slump
- Sag and slip resistant – Immediately holds wall tiles in place
- Extended open time formula
- Smooth and creamy for ease of handling
- Exceeds ANSI A118.15HET and A118.11 and ISO 13007 C2TES1P1 rated

Benefits of Product in the Installation

- High bond strength
- Suited for thin-set and large and heavy thicknesses up to 3/4" (19 mm)
- Recommended for interior and exterior pools and water features which require ANSI A118.15 bonding mortars

Ordering Information

| | ITEM CODE | SIZE | COLOR |
|--------|-----------|----------------------|-------|
| USA | VBHPG50 | 50 lb (22.68 kg) Bag | Gray |
| USA | VBHPW50 | 50 lb (22.68 kg) Bag | White |
| Canada | CVBHPG50 | 50 lb (22.68 kg) Bag | Gray |
| Canada | CVBHPW50 | 50 lb (22.68 kg) Bag | White |

Approximate Coverage

| TROWEL SIZE | MIN COVERAGE | MAX COVERAGE |
|---|-----------------|------------------|
| 1/4" x 1/4" x 1/4" (6 x 6 x 6 mm) Square-Notch | 90 ft² (8.4 m²) | 100 ft² (9.3 m²) |
| 1/4" x 3/8" x 1/4" (6 x 9.5 x 6 mm) Square-Notch | 60 ft² (5.6 m²) | 67 ft² (6.2 m²) |
| 1/2" x 1/2" x 1/2" (13 x 13 x 13 mm) Square-Notch* | 42 ft² (3.9 m²) | 47 ft² (4.4 m²) |
| 3/4" x 9/16" x 3/8" (19 x 14 x 9.5 mm) U-Notch @45° Angle | 34 ft² (3.2 m²) | 38 ft² (3.5 m²) |
| 3/4" x 9/16" x 3/8" (19 x 14 x 9.5 mm) U-Notch @30° Angle | 42 ft² (3.9 m²) | 47 ft² (4.4 m²) |

Chart for estimating purposes. Coverage may vary based on installation practices and jobsite conditions. For more sizes, use the material calculator at CustomBuildingProducts.com or contact CUSTOM Technical Services at 800-282-8786.

Note that mortar coverage does not include backbuttering tiles. When backbuttering, consider the tile underside pattern and depth to estimate thickness and usage to add to your estimate.

Recommended minimum coverage 80% for dry areas and 95% for wet areas and exteriors. Flat back troweling the tile underside may be necessary.

*See technical datasheet for information regarding trowel types for installing tiles 15" or larger.



Select a qualifying system of Prep, Set and Grout products and CUSTOM will warranty the tile installation for life, including tile, materials and labor. See website for complete details.

©2025 Custom Building Products. All rights reserved. The CUSTOM logo, and product logos are registered trademarks of Custom Building Products. CUSTOM may make product modifications at any time without notice. Product specifications are subject to change. Visit custombuildingproducts.com for updated technical data sheets and SDS information.

Suitable Substrates

- Concrete, mortar beds, masonry, portland cement plaster
- Liquid-applied and waterproofing membranes such as RedGuard® Waterproofing and Crack Prevention Membrane
- Custom® 9240
- Crack isolation sheet membranes such as Crack Buster® Pro
- Uncoupling mats such as RedGuard® Uncoupling Mat
- Substrates treated with MBP Multi-Surface Bonding Primer
- Exterior Grade Plywood (interior residential and light commercial dry areas)
- Gypsum wallboard (interior dry areas)
- Existing ceramic tile (scarified)
- Fully-bonded sheet vinyl flooring (scarified)
- Plastic laminates (scarified)
- Cutback adhesive (see preparation instructions)



DOWNLOAD CUSTOM'S MOBILE APP



Custom Building Products
800-272-8786
custombuildingproducts.com

SS225 7/25R

